


JD300-3-ZGSM-4-RYG288

ZGSM LED Signal Heads for Road Signal Systems



Characteristics

- ⊙ Utilizing imported LED chip, long lifespan.
- ⊙ Using constant current driver, working voltage 100-240VAC, low power
- ⊙ Novel structure and beautiful appearance, using inflaming retarding and UV-proof housing material.
- ⊙ Long visible distance, symmetrical light distribution.
- ⊙ Multi-ply sealed water resistant, IP rating: >IP54.
- ⊙ In accordance with GB/14887-2011 and relevant International standard.
- ⊙ Visible distance: >500M.
- ⊙ Working humidity: ≤95%
- ⊙ LED Driver: Constant current driver (Efficiency >85% PF >0.85).

⊙ Main Technology Index

Model	Light Color	LED Qty	Light Intensity (mcd)	Wavelength (nm)	Visual Angle	Power Consumption (W)	Operating Temperature (°C)	Working voltage	Housing material	Dimension
JD300-3-ZGSM-4-RYG288	R	Full Screen: 168	5000~7000	625±5	<30°	< 8W	-40~+75	100-240VAC 50/60Hz	PC	1480 x367 x150 mm 58.3 x14.4 x5.9 inches
		Countdown: 140				< 2W				
	Y	168	5000~7000	590±5		< 8W				
	G	Full Screen: 168	8000~13000	500±5		< 10W				
		Countdown: 140				< 2W				

⊙ Product Packing

Model	Qty	Packing Dimension	Gross Weight	Fixture Weight (single)	Packing material	Packing Volume
JD300-3-ZGSM-4-RYG288	2	1560 x380 x440 mm 61.4 x15.0 x17.3 inches	35.5 kg /78.3 lbs	16.5 kg /36.4 lbs	carton, foam	0.27 m ³