



STREETLIGHT PHOTOMETRIC TEST REPORT

NAME: LED SOLAR STREET LIGHTS	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ZGSM	SUR.:21cm*16cm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 135.00 lm/W
MODEL	ZGSM-PV10050	I _{max} (cd)	4875	η street_up(%)	0.0	
NOMINAL POWER(W)	50	LOR(%)	100.0	η street_down(%)	50.3	
RATED VOLTAGE(V)	12	TOTAL FLUX(lm)	6750	η house_up(%)	0.0	
NOMINAL FLUX(lm)	6750	MAXIMUM @(C,γ)	180,57.0	η house_down(%)	49.7	
LAMPS INSIDE	1	η up(%)	0.0	76 FLASHAREA(m2)	0.05000	
TEST VOLTAGE(V)	220.1	η down(%)	100.0	SLI	20.473	


INTENSITY DISTRIBUTION DIAGRAM
IN C PLANSMAX INTENSITY CONE SURFACE
DISTRIBUTION DIAGRAM

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

STREETLIGHT ISOCANDELA DIAGRAM

NAME: LED SOLAR STREET LIGHTS	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ZGSM	SUR.:21cm*16cm	Shielding Angle:



Classification:



IES:Type I - Short
 CIE:Narrow - Short
 IES:Full cut-off
 CIE:Full cut-off
 Max.At80:23.92cd/klm
 Max.At90:0cd/klm
 Max.80-90:23.92cd/klm

ISOCANDELA DIAGRAM	
UNIT	cd
Imax=100%	4875
90%	4388
80%	3900
70%	3413
60%	2925
50%	2438
40%	1950
30%	1463
20%	975
10%	488
5%	244

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.480m [K=1.0000]
 Remarks:

COEFFICIENT OF UTILIZATION CURVE AND ISOLUX DIAGRAM



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.480m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

NAME: LED SOLAR STREET LIGHTS	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ZGSM	SUR.:21cm*16cm	Shielding Angle:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	Φ lum,lamp
10	2140	2246	2309	2263	2168	2244	2304	2245	0- 10	209.4	209.4	3.1,3.1
20	2236	2291	2138	2346	2276	2377	2168	2381	10- 20	650.2	859.6	12.7,12.7
30	2441	1946	1264	2092	2550	1986	1193	2009	20- 30	989.9	1849	27.4,27.4
40	3335	1194	381.4	1498	3527	1245	362.2	1274	30- 40	1109	2959	43.8,43.8
50	3802	536.1	265.2	853.9	4033	629.3	287.2	660.6	40- 50	1183	4142	61.4,61.4
60	4841	270.0	208.9	323.8	4721	291.0	212.7	309.0	50- 60	1349	5491	81.4,81.4
70	1588	116.3	193.6	116.1	1295	124.6	194.7	128.7	60- 70	997.7	6489	96.1,96.1
80	146.2	70.72	160.2	67.62	87.53	76.20	161.4	72.71	70- 80	191.9	6681	99,99
90	0	0	0	0	0	0	0	0	80- 90	68.99	6750	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM


NAME: LED SOLAR STREET LIGHTS	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ZGSM	SUR.:21cm*16cm	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

Planar Illuminance Curve




C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.480m [K=1.0000]
 Remarks:

LCS REPORT

NAME: LED SOLAR STREET LIGHTS	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ZGSM	SUR.:21cm*16cm	Shielding Angle:

LUMINAIRE CLASSIFICATION SYSTEM(LCS) GRAPH


C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.480m [K=1.0000]
 Remarks:

BUG REPORT

NAME: LED SOLAR STREET LIGHTS	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ZGSM	SUR.:21cm*16cm	Shielding Angle:

IESNA Luminaire Flux Distribution Table:

Zone	Lumens	Luminaire %
FL - Front-Low(0-30)	921.91	13.7
FM - Front-Medium(30-60)	1827.5	27.1
FH - Front-High(60-80)	608.29	9.0
FVH - Front-Very High(80-90)	34.294	0.5
Total Forward Light	3392	50.3

BL - Back-Low(0-30)	927.59	13.7
BM - Back-Medium(30-60)	1814.2	26.9
BH - Back-High(60-80)	581.34	8.6
BVH - Back-Very High(80-90)	34.694	0.5
Total Back Light	3357.9	49.7

UL - Uplight-Low(90-100)	0	0.0
UH - Uplight-High(100-180)	0	0.0
Total Up Light	0	0.0

BUG(Back,Up,Glare) Rating	B2-U0-G2
---------------------------	----------

Zone	Downward Lumens	Upward Lumens	Total Lumens
House Side	3357.9	0	3357.9
Street Side	3392	0	3392


C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

ROAD ISOCANDELA REPORT

NAME: LED SOLAR STREET LIGHTS	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ZGSM	SUR.:21cm*16cm	Shielding Angle:

ROAD SURFACE ISOCANDELA DIAGRAM



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```