



STREETLIGHT PHOTOMETRIC TEST REPORT

NAME: LED SOLAR STREET LIGHTS	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ZGSM	SUR.:21cm*16cm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 130.00 lm/W			
MODEL	ZGSM-PV7040	I _{max} (cd)	3756	η street_up(%)	0.0
NOMINAL POWER(W)	40	LOR(%)	100.0	η street_down(%)	50.3
RATED VOLTAGE(V)	12	TOTAL FLUX(lm)	5201	η house_up(%)	0.0
NOMINAL FLUX(lm)	5200	MAXIMUM @(C,γ)	180,57.0	η house_down(%)	49.8
LAMPS INSIDE	1	η up(%)	0.0	76 FLASHAREA(m2)	0.05000
TEST VOLTAGE(V)	220.1	η down(%)	100.0	SLI	20.098




C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

STREETLIGHT ISOCANDELA DIAGRAM

NAME: LED SOLAR STREET LIGHTS	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ZGSM	SUR.:21cm*16cm	Shielding Angle:



Classification:



IES:Type I - Short
 CIE:Narrow - Short
 IES:Full cut-off
 CIE:Full cut-off
 Max.At80:23.92cd/klm
 Max.At90:0cd/klm
 Max.80-90:23.92cd/klm

ISOCANDELA DIAGRAM	
UNIT	cd
Imax=100%	3756
90%	3381
80%	3005
70%	2629
60%	2254
50%	1878
40%	1503
30%	1127
20%	751
10%	376
5%	188

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.480m [K=1.0000]
 Remarks:

COEFFICIENT OF UTILIZATION CURVE AND ISOLUX DIAGRAM



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.480m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

NAME: LED SOLAR STREET LIGHTS	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ZGSM	SUR.:21cm*16cm	Shielding Angle:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	Φ lum,lamp
10	1649	1731	1779	1744	1670	1729	1775	1730	0- 10	161.3	161.3	3.1,3.1
20	1723	1765	1647	1807	1753	1831	1670	1834	10- 20	501.0	662.3	12.7,12.7
30	1881	1499	973.7	1612	1965	1530	919.0	1548	20- 30	762.7	1425	27.4,27.4
40	2569	920.2	293.8	1154	2717	959.5	279.1	981.9	30- 40	854.5	2280	43.8,43.8
50	2929	413.0	204.3	657.9	3107	484.9	221.3	509.0	40- 50	911.7	3191	61.4,61.4
60	3730	208.0	160.9	249.5	3637	224.2	163.9	238.0	50- 60	1040	4231	81.4,81.4
70	1223	89.57	149.2	89.44	998.0	95.97	150.0	99.13	60- 70	768.7	5000	96.1,96.1
80	112.6	54.49	123.4	52.10	67.44	58.71	124.4	56.02	70- 80	147.9	5147	99,99
90	0	0	0	0	0	0	0	0	80- 90	53.15	5201	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM


NAME: LED SOLAR STREET LIGHTS	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ZGSM	SUR.:21cm*16cm	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2018

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.480m [K=1.0000]
Remarks:

Planar Illuminance Curve




C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.480m [K=1.0000]
Remarks:

LCS REPORT

NAME: LED SOLAR STREET LIGHTS	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ZGSM	SUR.:21cm*16cm	Shielding Angle:

LUMINAIRE CLASSIFICATION SYSTEM(LCS) GRAPH


C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.480m [K=1.0000]
 Remarks:

BUG REPORT

NAME: LED SOLAR STREET LIGHTS	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ZGSM	SUR.:21cm*16cm	Shielding Angle:

IESNA Luminaire Flux Distribution Table:

Zone	Lumens	Luminaire %
FL - Front-Low(0-30)	710.3	13.7
FM - Front-Medium(30-60)	1408	27.1
FH - Front-High(60-80)	468.67	9.0
FVH - Front-Very High(80-90)	26.423	0.5
Total Forward Light	2613.4	50.3

BL - Back-Low(0-30)	714.67	13.7
BM - Back-Medium(30-60)	1397.8	26.9
BH - Back-High(60-80)	447.9	8.6
BVH - Back-Very High(80-90)	26.73	0.5
Total Back Light	2587.1	49.7

UL - Uplight-Low(90-100)	0	0.0
UH - Uplight-High(100-180)	0	0.0
Total Up Light	0	0.0

BUG(Back,Up,Glare) Rating	B2-U0-G1
---------------------------	----------

Zone	Downward Lumens	Upward Lumens	Total Lumens
House Side	2587.1	0	2587.1
Street Side	2613.4	0	2613.4


C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

ROAD ISOCANDELA REPORT

NAME: LED SOLAR STREET LIGHTS	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: ZGSM	SUR.:21cm*16cm	Shielding Angle:

ROAD SURFACE ISOCANDELA DIAGRAM



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```